

The PSP-Series are single output, 200W, programmable switching DC power supplies. OVP, OCP, OTP, and OPP protect the PSP-Series and its loads from unexpected conditions. The PSP-Series have large a LCD panel with output and parameter views and a key lock feature to prevent changing the settings. The PSP-Series is suitable for generic bench-top applications in laboratories and educational institutions.

PSP-603/405/2010







FEATURES

- * LCD Display
- * Output ON/OFF Control
- * 3 Step Fan Speed Control
- * Voltage/Current/Power Setting
- * Key Lock to Avoid Error Operation
- * Normal, +% & -% Output Operation Key
- * Standard Interface: RS-232C
- * Optional European Type Jack Terminal

Distributed by:





99, rue Beranger 92320 Chatillon - France

Tel: +33 (0)1 71 16 17 00 Fax: +33 (0)1 71 16 17 03

www.testoon.com

Rear Panel



SPECIFICATIONS OUTPUT			
Model	DCD CO2	DCD 40F	DCD 2010
Model	PSP-603	PSP-405	PSP-2010
Voltage	0 ~ 60V	0 ~ 40V	0 ~ 20V
Current	0 ~ 3.5A	0 ~5A	0 ~ 10A
VOLTAGEREGULATION			
Load	< 10mV	< 10mV	< 10mV
Line	≤ 10mV ≤ 0.05%	≤ 10mV ≤ 0.05%	≤ 10mV ≤ 0.05%
CURRENT REGULATION			
Load	≤ 5mA	≤ 5mA	≤ 5mA
Line	< 0.05%	< 0.05%	< 0.05%
RIPPLE	_ = 0.0570	_ = 0.0070	_ 0.0070
	Z = 1/	< a	/ aa .u
Voltage (mVrms)	≤ 20mV	≤ 20mV	≤ 20mV
Current (mArms)	= 10mA	= 10mA	= 10mA
RESOLUTION			
Voltage	20mV	10mV	10mV
Current	2mA	2mA	5mA
PROGRAM ACCURACY			
Voltage	± 0.05%rdg ± 4digits	± 0.05%rdg ± 3digits	± 0.05%rdg ± 3digits
Current	<u>+</u> 0.1%rdg + 5digits	\pm 0.1%rdg + 5digits	<u>+</u> 0.3%rdg + 10digits
READBACK (METER) RESOLUTION			
Voltage	Same as Resolution	Same as Resolution	Same as Resolution
Current	Same as Resolution	Same as Resolution	Same as Resolution
READBACK (METER) ACCURACY			
Voltage	Same as Program Accuracy	Same as Program Accuracy	Same as Program Accuracy
Current	Same as Program Accuracy	Same as Program Accuracy	Same as Program Accuracy
PROTECTION		\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \
OVP/OCP/OPP/OTP	<u> </u>	<u> </u>	V
OUTPUT ON/OFF CONTROL	V	V	V
DISPLAY	V	V	•
LCD			
INTERFACE (STANDARD)			
RS-232C			
POWER SOURCE			
AC 115V±10%, AC 230V±15%, 50/60Hz			
DIMENSIONS & WEIGHT			
225(W) x 100(H) x 305(D) mm ; Approx. 4kg			

ORDERING INFORMATION

 PSP-603
 200W Programmable Switching DC Power Supply

 PSP-405
 200W Programmable Switching DC Power Supply

 PSP-2010
 200W Programmable Switching DC Power Supply

ACCESSORIES:

User manual x 1, Power cord x 1, Test lead GTL-104 x 1 , European test lead GTL-204 x 1

OPTIONAL ACCESSORIES
GTL-232A RS-232C Cable

FREE DOWNLOAD

PC Software RS-232 Remote Control Software