



Hammer-shaped wood moisture meter with temperature compensation and wood type selection capability!



- R Measuring range from 6% to 60% of moisture contents
- (R) No wires, no electrodes, no formulas, no correction tables
- Replaceable needles made of high quality steel
- (R) Chromium plated steel body
- (R) Temperature compensation from -10° to 60°C
- ® State-of-the-art comfortable, ergonomic design
- R Big LCD soldered to the board assuring long reliable operation
- ® Circuit board fastened with a special shock absorber
- R Easy wood species selection (9 groups incl. 270 exotic species)
- R Very low power consumption
- ® Modular design quick and easy servicing and assembly
- ® Quick and easy battery replacement
- R Auto power off
- ® (€ certified
- R Excellent price-performance ratio



TECHNICAL DATA

Range	6% - 60% moisture contents
Resolution	0.1%
Accuracy (in 20°C)	
within range: 6% - 15%	±1%
within range: 16% - 28%	±2%
within range: 29% - 60%	approx. 10% of measured value
Number of wood species	9 groups (12 common + 270 exotic species)
Wood temperature range	-10°C - 60° C
Display	LCD
Power	12 V, battery 23A
Battery life	approx. 5000 measurements
Size	210 x 120 x 60 mm
Weight	approx. 0.8 kG
Guarantee	12 months







99, rue Beranger 92320 Chatillon - France Tel: +33 (0)1 71 16 17 00; Fax: +33 (0)1 71 16 17 03

www.testoon.com

