

# Non-Contact Forehead IR Thermometer

**✓ Ideal for quickly detecting elevated body temperature**  
Non-contact design eliminates need for replacement probe covers and other supplies

## Features:

- Measures body temperature from 89.6°F to 108.5°F (32.0°C to 42.5°C) without contact
- Accurate to 0.5°F (0.3°C) with 0.1°F/°C resolution
- Adjustable alarm alerts user visually and audibly when temperature exceeds programmed limit
- Optimum measurement distance of 1.9" to 5.9" (5 to 15cm)
- Measures surface temperature from 32°F to 140°F (0.0°C to 60.0°C)
- Fast response (0.5 seconds)
- Simply press the trigger and read temperature on the large backlit LCD display
- Memory stores up to 32 readings for easy recall
- Complete with 2 AA batteries and pouch

## Applications:

- Measure body (forehead) temperature
- Monitor individuals for temperature change
- Non-contact technique reduces potential spread of diseases from using contact devices




**Note:** This thermometer is intended for scanning individuals or monitoring an individual for potential elevated temperatures. It is not a substitute for a clinical thermometer. Always use a clinical thermometer when high accuracy body temperature measurements are required.

IR Thermometers that detect elevated body temperature will vary with various factors and should not be relied upon as the sole determinant of a person's body temperature. Use of additional medical devices and/or healthcare professionals will be needed to properly diagnose the condition of persons in any health screening assessment to identify elevated body temperature for any person.

## Ordering Information:

IR200 .....Forehead Temperature InfraRed Thermometer



Quick non-contact Temperature detection between the optimum distance stated above.

**testoon**.COM  
The measurement website

99 rue Beranger - 92320 Chatillon - France  
Tel. : +33 (0) 1 71 16 17 00 - Fax : +33 (0) 1 71 16 17 03  
[www.testoon.com](http://www.testoon.com)

Specifications	
Body Temperature Range	89.6 to 108.5°F (32 to 42.5°C)
Basic accuracy	±0.5°F/0.3°C
Surface Temperature Range	32 to 140°F (0 to 60°C)
Basic accuracy	±1.5°F (±0.8°C)
Resolution	0.1°C/°F
Response Time	500ms
Power	2 AA batteries
Dimensions	6.3x3.2x1.7" (160x82x42mm)
Weight	6.24oz (177g)

