A fantastic value simple-to-use PAT tester with a comprehensive range of tests, data storage and label printing facilities.



The **PrimeTest 250+** offers fast and efficient electrical safety testing with label printing and data storage.

Enabling simple, professional and fast PAT testing, this versatile tester features all of the required tests of the IET 5th Edition Code of Practice along with USB download. It is also fully compatible with the Test n Tag Pro serial printer for quick and easy label printing without any setup – just plug and print.

A Seaward datalogger program is available as standard and this along with the simple key download feature allows measurement data to be quickly and easily transferred from the PrimeTest 250+ to PC at the press of a button; whilst all records are date stamped for complete traceability.

Data is downloaded in CSV format and can be accessed by a wide range of software packages or alternatively imported directly into PATGuard 3 for truly professional reports and certificates.

As with all Seaward battery powered PAT testers, accurate earth continuity tests are a given thanks to the unique "zap" circuit design.

# Why buy the PrimeTest 250+?

- > Very easy to use
- > **Plug and print** easy label printing with no setup
- > Date stamped results for full traceability
- > Single key save and download
- Download software included
- > Store 999 appliance records
- > Industry standard download format
- Comprehensive range of electrical tests
- > Test 3 phase appliances







A fantastic value simple-to-use PAT tester with a comprehensive range of tests, data storage and label printing facilities.

#### **Fast, Simple PAT Testing**

With Seaward's press to test technology, the PrimeTest 250+ is extremely simple to grasp. Its light weight and small size along with battery power means it is highly portable.

The PrimeTest 250+ offers a comprehensive suite of fast and accurate electrical safety tests to enable almost any workplace appliance to be tested, including accurate and reliable earth continuity tests, 3 phase appliances and Residual Current devices.

The ability to change pass/fail limits, test voltages 250v/500v, skip earth continuity if the appliance has no exposed earthed parts and even carry out an earth continuity on Class 2 FE appliance meaning that you are in control of the tests that are carried out.

### **Plug and Print**

The PrimeTest 250+ can be used in conjunction with the Test n Tag Pro serial printer to further speed up the process of testing and labelling.

#### **Simple Data Management**

The PrimeTest 250+ has an internal memory capable of storing up to 999 appliance test records and the single key save allows records to be stored at the press of a button.

Transfer data via a USB cable directly to a PC using the supplied datalogger software. The data downloads in the industry standard CSV format and can be read directly into spreadsheets or other PC applications.

For those who require professional reports and certificates as well as complete data traceability and integrity, the downloaded data is also fully compatible with Seaward's PATGuard 3 software; which allows complete test records to be easily managed on a PC - offering total peace of mind and quicker, easier management of scheduling inspections and tests.

#### **Accurate and Reliable Earth Continuity Testing**

Some test instruments struggle to provide accurate and consistent earth continuity readings but thanks to a unique 'zap circuit' from Seaward, erratic earth continuity readings on those difficult to test appliances are a thing of the past.

Simply clip on and press to test. No more pressing or scraping with test probes or clips on chrome plated kitchen appliances trying to obtain a satisfactory reading - and no more surface damage on the appliance under test.



# Electrical Test Functions

- Low current earth continuity test guaranteeing accurate measurement
- > Class 2 FE earth continuity
- > Insulation resistance at 250V/500V
- > IEC lead test
- > Protective conductor current
- > Touch current
- > 3 Phase leakage current (requires adaptor)
- > Alternative leakage current
- > RCD test (30mA/150mA)
- > Power socket test

#### PrimeTest 250+ Users

- > Professional PAT testers
- > Service engineers
- > Facilities managers







A fantastic value simple-to-use PAT tester with a comprehensive range of tests, data storage and label printing facilities.

### **Technical Specification:**

#### **Earth Continuity**

Output Current 200mA minimum to into  $2\Omega$ 

Test Voltage (o/c) 9VDC nominal Test Duration (Class I Test) 2s nominal Display Range 0.01 – 19.99 $\Omega$  Pass Value (Class I Test) 0.1/0.2/0.3  $\Omega$ 

#### **Insulation Resistance**

Test Voltages 250/500VDC @1mA nominal

Test Current <2mA (s/c)

Test Duration (Class I or II) 2s

Display Range  $0.01-19.99 M\Omega$  Pass Value  $1.0 M\Omega \ \text{Class}$   $2.0 M\Omega \ \text{Class II}$ 

#### **Substitute Leakage**

Test Voltage 40V Nominal AC 50Hz Open Circuit

Test Duration 2s

Display Range 0.1 - 19.99mA
Pass Value 5.0mA

#### **IEC Lead Test**

Test Voltage 5VDC nominal
Test Duration Time for test (2s max)

Test Line/Neutral Checks for o/c, s/c and crossed

#### **Protective Conductor Current**

Test Voltage Supply Voltage, max current 13A

Test Duration 120s maximum
Display Range 0.15 - 19.99mA
Pass Value 5.0mA

#### **Touch Current**

Test Voltage Supply voltage, max current 13A

Test Duration 120s maximum
Display Range 0.10 - 5.0mA
Pass Value 5.0mA







A fantastic value simple-to-use PAT tester with a comprehensive range of tests, data storage and label printing facilities.

#### 3 Phase Leakage Current (Requires 3 Phase adaptor accessory)

Test Voltage 3 Phase supply voltage
Test Duration Continuous measurement

Display Range 0.10 - 9.99mA
Pass Value 5.0mA

**RCD Trip Time** 

RCD Type Plugtop and fixed installation

Test Voltage Mains supply voltage
Test Current 30/150mA rms sinusoidal

Test Current Phase 0°/180° auto switched on alternate tests

Measuring Range0 - 500msPass Value200ms

**Power Socket Check** 

Input Voltage Range 225 - 254VAC max current 13A UK
Indicates Configuration of Voltage Potential Line potential phase to earth
Line potential phase to neutral

Line potential phase to neutr

**General Specifications** 

Dimensions 265mm x 105mm x 52mm (h x w x d)

Weight 800g

Memory Size999 test recordsPower Source6 x AA Batteries

#### Standard Accessories (Supplied with PrimeTest 250+)

Datalogger software (via download), 0.5m extension adaptor, earth lead with probe and clip, mains lead, 6x AA batteries, USB download lead, carry case, operating instructions

#### **Part Numbers**

**Optional Accessory Kits** 

Pro Bundle (For automatic label printing)

403A956

PrimeTest 250+ tester, PATBag carrying case,

Cloverleaf adaptor, Pro Labels (labels 52 x 25mm),

Test n Tag Pro Serial Printer, PrimeTest Checkbox, Guide to PAT Testing Booklet, Training card

Pro Bundle with 1 year PATGuard 3 software 403A957

PrimeTest 250+ tester, PATBag carrying case, Cloverleaf adaptor, Pro Labels (labels 52 x 25mm), Test n Tag Pro Serial Printer, PrimeTest Checkbox,

Guide to PAT Testing Booklet, Training card, 1 year PATGuard 3 licence

**Instrument Only** 

PrimeTest 250+ 403A910







A fantastic value simple-to-use PAT tester with a comprehensive range of tests, data storage and label printing facilities.

#### **Optional Accessories**

| Test n Tag Pro Printer                              | 339A933 |
|---|---------|
| Roll of small labels (approx. 400 off 52 x 25mm)    | 339A947 |
| 110V to IEC adaptor                                 | 344A050 |
| 230 to 110V adaptor                                 | 270A076 |
| PATCheckbox   | 227A910 |
| 3 Phase Leakage Adaptor 5 Star 16A                  | 391A920 |
| 3 Phase Leakage Adaptor 5 Star 32A                  | 391A910 |
| 3 Phase Adaptor Delta 4 pin 16A 415V (for Rpe & IR) | 209A910 |
| 3 Phase Adaptor Star 5 pin 16A 415V (for Rpe & IR)  | 209A911 |
| 3 Phase Adaptor Delta 4 pin 32A 415V (for Rpe &IR)  | 209A912 |
| 3 Phase Adaptor Star 5 pin 32A 415V (for Rpe &IR)   | 209A913 |
| PATBag Carry Case                                   | 71G099  |

PATGuard 3 software - download 30 day free trial at seaward.com/pg3trial

#### Training

Seaward offer a range of PAT testing courses, including City & Guilds. Go to **seaward.com/training** for more information.

#### Services

2 year warranty (subject terms and conditions, available at seaward.com/register)

Service and calibration by Calibration House.

Go to **calibrationhouse.com** for more information.



99 rue Beranger - 92320 Chatillon - France Tel.: +33 (0) 1 71 16 17 00

E-mail: contact@testoon.com







