



### Key Features

- Instantly measures maximum power, temperature, and I-V curve
- Provides graphical data analysis with I-V curve up to 800 W per panel
- Diagnoses and troubleshoots solar panels with included MC4 PV plugs and clips
- High-contrast, large LCD display is easy to read in direct sunlight
- Powered by a built-in lithium battery

### Main Applications

- Verify the performance and safety of solar power systems
- Ensure the quality of solar panels during production

Distributed by:

**testoon**.COM

The measurement website

99 rue Beranger 92320 Chatillon - France

Tel. : +33 (0) 1 71 16 17 00

E-mail: [contact@testoon.com](mailto:contact@testoon.com)

[www.testoon.com](http://www.testoon.com)

### SPECIFICATIONS

Electrical Measurement	Range	Accuracy
Maximum Power Value (Pmax)	0 W to 800 W	±5%
Voltage at MMPT point (Vmax)	0 V to 60 V	±5%
Current at MMPT point (Imax)	0 A to 30 A	±5%
Open Circuit Voltage (VOC)	0 V to 60 V	±1%
Short Circuit Current (ISC)	0 A to 30 A	±1%
Device Temperature Protection	0°C to 60°C	±3%
Measuring rate	3 samples per second	
<b>Power System</b>		
Display	TFT Display	
Backlight	White LED array	
Warranty	Limited 3-Year Warranty <a href="https://www.flir.com/testwarranty">https://www.flir.com/testwarranty</a>	
Calibration cycle	Once per year, recommended	
<b>Certifications</b>		
Certifications	CE, RCM, FCC	
Safety standards	IEC 61010-1	
EMC standards	EN61326-1	

Environmental Data	
Operating ambient temperatures and relative humidity (RH)	-10°C to 50°C (14°F to 122°F), <80% RH
Storage temperature and RH	-20°C to 60°C (-4°F to 140°F), 0 to 80% RH
Operating altitude	2000 m (6560 ft)
Pollution degree	2
Meter Physical Data	
Weight	206 g (0.45 lbs)
Dimensions (L x W x H)	151.6 mm x 72.5 mm x 38 mm (5.97 in x 2.85 in x 1.50 in)
Included in the box	PV48 Carrying Pouch CAT III-300 V Double-Molded Alligator Clips CAT III-300 V MC4 PV Plugs 1 x 3.7 V Li-ion Battery User Manual

Specifications subject to change. For the most up-to-date specifications, please visit [flir.com](http://flir.com).

For technical or sales support, please visit:  
[www.flir.com/about/general-inquiries](http://www.flir.com/about/general-inquiries)

This product is subject to United States export regulations and may require US authorization prior to export, reexport, or transfer to non-US persons or parties. Diversion contrary to US law is prohibited.

For assistance with confirming the Jurisdiction & Classification of Teledyne FLIR, LLC products, please contact [exportquestions@flir.com](mailto:exportquestions@flir.com). ©2025 Teledyne FLIR, LLC. All rights reserved.

Revised 03/04/25  
FLIR\_PV48\_Datasheet\_en-US-LTR RH24-0864-INS